ELEVATION CERTIFICATE

O.M.B. No. 3067-0077 Expires July 31, 1999

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form.

Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION					FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME RICHARD COCHINOS					POLICY NUMBER
STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER 7711 DELRIDGE CIRCLE					COMPANY NAIC NUMBER
OTHER DESCRIPTION (Lot and LOT 26, DELR	Biock Numbers, etc.) IDGE SUBDIVI	SION			
ANCHORAGE STATE					ZIP CODE 99507
SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION					
Provide the following from the proper FIRM (See Instructions):					
1. COMMUNITY NUMBER 02005	2. PANEL NUMBER 0243	3. SUFFIX C	4. DATE OF FIRM INDEX 3/5/90	5. FIRM ZONE A-1	6. BASE FLOOD ELEVATION (in AO Zones, use depth) 174.35
7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Cother (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: Like in the community's BFE: Feet NGVD (or other FIRM datum—see Section B, Item 7).					
SECTION C BUILDING ELEVATION INFORMATION					
2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 176.2 feet NGVD (or other FIRM datum—see Section B, Item 7). (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of 16.1 feet NGVD (or other FIRM datum—see Section B, Item 7). (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is 16.1 feet above 17.1 feet above 17.1 feet above 17.1 feet above 17.2 feet above 18.1 feet above 19.1 feet ab					
 5. The reference level elevation is based on: actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.) 6. The elevation of the lowest grade immediately adjacent to the building is: 17.6.0 feet NGVD (or other FIRM datum-see 					
Section B, Item 7).					
SECTION D COMMUNITY INFORMATION					
 If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: feet NGVD (or other FIRM datum—see Section B, Item 7). Date of the start of construction or substantial improvement					


SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME LICENSE NUMBER (or Affix Seal) ROBERT E. JOHNS. 4121 - SOWNER ROBERT E. JOHNS JR. & ASSOCIATES ADDRESS ZIP 842 ΝUÉ ANCHORAGE AK 99501-4260 DATE PHONE 9-27-1999 (907)276-6329 Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner. COMMENTS: U.S.C & G.S. M.S.L. 1972 DATUM, BENCH MARK GAAB 20



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.